

# बाटो होस् जस्तो सुकै अफ्यारो BOLERO PIK-UP नै छ राम्रो 4X4



with  
**Power steering**

Mahindra Bolero Pik-Up  
डढमशील नेपालीको  
भरपर्दो साथी

## MAHINDRA BOLERO 4x4 PIK-UP SPECIFICATION

<b>Engine</b>	m2DiCR 4 Cyl 2.5L TB	<b>Wheels &amp; Types</b>	Type	*Radial tyre with tube, 5.5J x 15* 38.1cm (15*) for 7.00 R15 10 PR
Engine Capacity	2523 cm <sup>3</sup>	<b>Fuel Tank Capacity</b>	Litres	57
Max output	46.3 kW (63 BHP)@3200 r/min	<b>Dimension (mm)</b>	Wheel Base	3014
Max torque	195Nm (19.38 kgm) @ 1400 - 2200 r/min	Overall length	4859	
<b>Transmission &amp; Driveline</b>		Overall width	1670	
Clutch	Single Plate Dry Clutch	Overall height	1810	
Gearbox	5 Speed All Synchroneshed 5 Forward, 1 Reverse	Outer Load body (l x b x h)	2281x1532x750	
<b>Steering</b>		<b>Turning Circle radius (m)</b>	6.5m	
Type	Power steering	<b>Weight (kg)</b>		
<b>Suspension</b>		payload Weight	1010	
Front	Rigid leaf spring suspension, Anti-roll bar provided at front	Max GVW	2750	
Rear	Hydraulic Double Acting, Telescopic shock obsorbers with leaf spring	Kerb weight	1740	
<b>Brakes</b>		<b>Seating Capacity</b>	1+1	
Front	Disc brakes	<b>Warranty</b>	3 year/3 lakh kms	
Rear	Drum brakes			

# कुरा हो यो फाइदाको, क्याम्पर हो यो काइदाको

## BOLERO CAMPER DC



with  
**Power steering**

Mahindra Bolero Pik-Up  
डढमशील नेपालीको  
भरपर्दो साथी

## MAHINDRA BOLERO CAMPER SPECIFICATION

<b>Engine</b>	m2DiCR 4 Cyl 2.5L TB	<b>Wheel &amp; Type</b>	Tyre Type	Radial with tube (Radial tubeless for Cash Van variant)
Engine Capacity	2523 cc	Rim Size	6.0 J x 15	
Max output	46.3 kW@3200 r/min	Tyre Size	P235/75 RIS	
Max torque	195Nm @ 1400 - 2200 r/min	<b>Fuel Tank Capacity</b>	Litres	57
<b>Transmission &amp; Driveline</b>		<b>Dimension</b>	Wheel Base (mm)	3014
Clutch	Single Plate Dry Clutch	Front track	1443	
Gearbox	5 Speed All Synchroneshed 5 Forward, 1 Reverse	Rear track	1135	
<b>Steering</b>		Overall L x W x H (mm)	4859 x 1670 x 1810	
Type	Power	Outer Cargo box dimensions (mm)	1481 x 1532 x 750	
<b>Suspension</b>		Minimum ground clearance (mm)	215	
Front (with spring stiffness)	Rigid axle with leaf spring	<b>Weight</b>		
Rear (with spring stiffness)	Rigid axle with leaf spring	Kerb Weight (kg)	2WD - 1675, 4WD - 1771	
<b>Shock Absorbers</b>		GVW	2710	
Hydraulic Double Acting, Telescopic Type		Payload (kg)	2WD - 1035, 4WD - 945	
<b>Brakes</b>		<b>Seating Capacity</b>	D+4	
Front	Disc brakes	<b>Warranty</b>	3 year/3 lakh kms	
Rear	Drum brakes			



हरेक सडक गल्लीमा Fit,  
तपाईंको बजेटमा SUPER HIT!

**BOLERO PIK-UP**  
EXTRA **LONG** 1.5T



with  
**Power steering**

Mahindra Bolero Pik-Up  
उद्यमशील नेपालीको  
भरपर्दो साथी

### MAHINDRA BOLERO PIK-UP - EXTRA LONG SPECIFICATION

<b>Engine</b>	m2DiCR 4 Cyl 2.5L TB	<b>Brakes</b>	LCRW
Engine Capacity	2523 cc	Type	Disc brakes
Max output	46.3 kW (6.3 BHP)@3200 rpm	Front	Disc brakes
Max torque	195Nm (19.38 kgm) @ 1400 - 2200 rpm	Rear	Drum brakes
<b>Transmission &amp; Driveline</b>		<b>Rear axle type</b>	Double bearing
Clutch	Single Plate Dry Clutch	<b>Wheel &amp; Tyre</b>	
Gearbox	5 Speed All Synchronised 5 Forward, 1 Reverse	Type	Radial tyre with tube 5.5J x 15* (38.1cm for 700RTS, 12 PR)
<b>Steering</b>		<b>Fuel Tank Capacity</b>	Litres 57
Type	Power steering	<b>Dimension (mm)</b>	
<b>Suspension</b>		Wheel Base	3264
Front	5 leaves Rigid leaf spring suspension, Anti-roll bar provided at front	Overall length	5219
Rear	8 leaves Rigid leaf spring suspension Hydraulic Double Acting, Telescopic shock absorbers	Overall width	1700
		Overall height	1865
		Load body (l x b x h)	2765x1700x650mm
		<b>Turning Circle radius (m)</b>	6.5m
		<b>Weight (kg)</b>	
		payload Weight	1500
		Max GVW	3225
		Kerb weight	1725
		<b>Warranty</b>	3 year/3 lakh kms
		<b>Seating Capacity</b>	D+1 (wider seat)

व्यवसाय अनेक, गाडी एक  
महिन्द्रा **BOLERO PIK-UP**  
EXTRA **STRONG** 1.3T



with  
**Power steering**

Mahindra Bolero Pik-Up  
उद्यमशील नेपालीको  
भरपर्दो साथी

### MAHINDRA BOLERO PIK-UP - EXTRA STRONG SPECIFICATION

<b>Engine</b>	m2DiCR 4 Cyl 2.5L TB	<b>Brakes</b>	LCRW
Engine Capacity	2523 cc	Type	Disc brakes
Max output	46.3 kW (6.3 BHP)@3200 r/min	Front	Disc brakes
Max torque	195Nm (19.38 kgm) @ 1400 - 2200 rpm	Rear	Drum brakes
<b>Transmission &amp; Driveline</b>		<b>Rear axle type</b>	Double bearing
Clutch	Single Plate Dry Clutch	<b>Wheel Type</b>	
Gearbox	5 Speed All Synchronised 5 Forward, 1 Reverse	Tyre Type	Radial tyre with tube 5.5J x 15* (38.1cm for 700RTS, 10 PR)
<b>Steering</b>		<b>Fuel Tank Capacity</b>	Litres 57
Type	Power steering	<b>Dimension (mm)</b>	
<b>Suspension</b>		Wheel Base	3260
Front	5 leaves Rigid leaf spring suspension, Anti-roll bar provided at front	Overall length	5219
Rear	7 leaves Rigid leaf spring suspension Hydraulic Double Acting, Telescopic shock absorbers	Overall width	1670
		Load body (l x b x h)	2540x1700x650mm
		<b>Turning Circle radius (m)</b>	6.5m
		<b>Weight (kg)</b>	
		payload Weight	1290 for PS, 1300 for MS
		Max GVW	2990
		Kerb weight	1700
		<b>Warranty</b>	3 year/3 lakh kms
		<b>Seating Capacity</b>	D+1 (wider seat)